

PRODUCT NO: DA-DB-05RP-SMA

ELECTRIC

FREQUENCY: 2.4/5GHz RETURN LOSS: -10dB MAX CERTAIN DIRECTION: OMNI

IMPEDANCE: 50 ohm VSWR: 2.0 MAX MAX GAIN: 5dBi

MECHANICAL

ANTENNA BASE: ABS ANTENNA COVER: ABS

STORAGE TEMPERATURE: -30°C~75°C OPERATING TEMPERATURE: -20°C~65°C STANDARD CONNECTOR: RP SMA MALE

Prohibit re-circulating



/ ODINI EIANI		
NOTE	DIMENSION	
1.1.STRIP ALL BURRS. 2.ALL DIMENSIONS ARE AFTER	UNLESS OTHERWISE NOTED TOLERANCES	
PLATING. 3.DIAMETERS ON COMMON CENTERS.	X=±0.3	
TO BE CONCENTRIC WITHIN 0.1 T.I.R 4.CHAMFER 1ST & LAST THREADS 45°.	$0.X=\pm0.2$	
5.BREAK ALL CONNERS & EDGES CO.15 MAX.	0.XX=±0.1	

		斗技有限。 Technologies	
TITLE			
2.4/5GHz Dipole Antenna 5dBi			

TITLE		
2.4/5GHz Dipole Antenna 5dBi		
DRAWING NO. DA-DB-05RP-SMA		
APPROVED	DRAWN DATE 01/04/13	
CHECKED	SCALE	
DRAWN	UNIT	
ALICE	mm	

All creative content and details belonging to HYT's confidential, and the owner, without consent, Do not posted, theft, copied and sent to a third party.